

Optiprimer G

Product name	Optiprimer G		Safety Data Sheet according regulation (EC) Directive			
Version	1,0	1907/2006				
Version date	5 januari 2011					
Revision of SDS with date	-	Printing date	10 januari 2012			
1. IDENTIFICATION OF THE SUB	STANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING					
1.1. Product identifier						
Productnaam en/of code	Optiprimer G in all available colors					
1.2. Relevant identified uses of	the substance or mixture and uses advised against					
	Waterborne spray quality for industrial use					
	For professional and industrial use only.					
	DRYWOOD Optiprimer G is a waterborne silk matt industrial primer a exterior wooden joinery and other wood constructions.	nd midcoat (spray quality) f	or interior and			
	For more information, please refer to the product information sheet	PIB 050000EN				
1.3. Details of the supplier of th	e safety data sheet					
Company Name	DRYWOOD COATINGS B.V					
Address	H. ter Kuilestraat 181, NL-7547 SK Enschede, The netherlands					
	P.O. Box 3954, NL-7500 DZ Enschede, The Netherlands					
Telephone number	+31 (0)53 433 44 22					
E-mail	safety@drywood.nl					
1.4. Emergency telephone numb						
Telephone number	+31 (0)53 433 44 22					
2. HAZARDS IDENTIFICATION						
2.1. Classification of the substar This preparation is not classified	nce or mixture as dangerous according to EC Directive 1999/45/EC.					
2.2. Label elements						
Symbols	Not applicable					
R-phrases	Not applicable					
S-phrases (advisory)	S2 Keep out of the reach of children. Avoid inhalation.					
	S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.					
	S51 Use only in well ventilated areas.					
2.3. Other hazards						
None						
3. COMPOSITION/INFORMATIO	N ON INGREDIENTS					
	or onvironmental bazard within the meaning of the Dangerous Substances Directiv		/			

Substances presenting a health or environmental hazard within the meaning of the Dangerous Substances Directive 67/548/EEC or Regulation (EC) No. 1272/2008, assigned a Community workplace exposure limit, classified as PBT/vPvB or included in the Candidate List.

3.2 Mixtures

Substance name	Concentration	CAS No / EC No /	Classification (67/548/EG)	Classification (Regulation (EG) Nr
		Registraion No		1272/2008)
Petroleum-distillates	0.5 - 1.5%	64742-47-8 /265-149-8/ -	Xn R65,R66	-

(*) See chapter 16 for full text of the R- and H-phrases



4. FIRST AID MEASURES

4.1. Description of first aid measures					
General	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.				
Inhalation	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.				
Skin contact	Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.				
Eye contact	Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart and seek medical advice.				
Ingestion	If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.				
4.2. Most important symptoms and effects, both acute and delayed					

Unknown

4.3. Indication of any immediate medical attention and special treatment needed

Unknown

5. FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media Not be used for safety reasons

Recommended: alcohol resistant foam, CO2, powders, water spray. Waterjet

5.2. Special hazards arising from the substance or mixture

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required.

5.3. Advice for fire-fighters

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses.

6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Avoid breathing vapours. Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13).

6.2. Environmental precautions

Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers or sewage, : inform appropriate authorities in accordance with local regulations

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent; avoid use of solvents

6.4 . Reference to other sections

Refer to protective measures listed in sections 7 and 8 and refer to disposal considerations in section 13.

7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Keep container tightly closed. Avoid skin and eye contact. Avoid inhalation of vapour and spray mist. Smoking, eating and drinking should be prohibited in application area. For personal protection see Section 8. Never use pressure to empty: container is not a pressure vessel. Always keep in containers of same material as the original one. Comply with the health and safety at work laws.

7.2. Conditions for safe storage, including any incompatibilities

Observe label precautions. Store between 5 and 30 °C in a dry, well ventilated place away from sources of heat and direct sunlight. Keep away from sources of ignition. Keep away from oxidizing agents, from strongly alkaline and strongly acid materials. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

7.3. Specific end use(s)

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.



8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1. Control parameters				
Substance name	TWA (8 hours (¹)		TWA (15 mir	n) (²)
Petroleum-distillates	1200 mg/m3	165 ppm	-	-
Source: Petroleum-distillate producer				
(1) Time Weighted Average (8 hours)				
(2) Time Weighted Average (3 hours)				
8.2. Exposure controls				
Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.				
Occupational exposure controls				
Respiratory protection	If workers are expos	ed to concentrati	ons above the	exposure limit they must use appropriate, certified respirators.
Hand protection	For prolonged or repeated handling, use butyl rubber or neoprene gloves. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.			
Eye protection	Use safety eyewear	designed to prote	ect against spla	sh of liquids
Skin protection	Personnel should we	ear anti-static clot	hing made of r	natural fibre or of high temperature resistant synthetic fibre.
Environmental exposure controls				

The product should not be allowed to enter drains or water courses.

9. PHYSICAL AND CHEMICAL PROP	PERTIES		
General data			
Appearance	Liquid		
Odor	Product -specific		
9.1. Information on basic physical	and chemical properties		
рН	7.5 - 8.5		
Flash point	Not applicabel bec	ause of the nature of this product	
Viscosity (20°C)	15000 - 20000	mPa.s	Method: Brookfield DV-I sp64 6rpm
Specific gravity	1.15 - 1.30 kg/l	(depending the color)	Method: Pyknometer
Vapour density	Not applicabel bec	ause of the nature of this product	
Lower explosion limit	Not applicabel bec	ause of the nature of this product	
Water solubility	miscible in water		
9.2. Other information			
-			
10. STABILITY AND REACTIVITY			

10. STABILITY AND REACTIVITY

10.1. Reactivity

10.2. Chemical stability

Stable under recommended storage and handling conditions (see section 7).

10.3. Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.4. Conditions to avoid

When exposed to high temperatures may produce hazardous decomposition products.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Such as carbon monoxide and dioxide, smoke, oxides of nitrogen etc.



11. TOXICOLOGICAL INFORMATION

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the Dangerous mixtures Directive 1999/45/EC and classified for toxicological hazards accordingly. See Sections 2 and 15 for details.

11.1. Information on toxicological effects

The preparation is not classified according the Dangerous Preparations Directive 1999/45/EC. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage.

12. ECOLOGICAL INFORMATION

There are no data available on the mixture itself.Do not allow to enter drains or water courses. See Sections 3 for details. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is classified as NOT dangerous for the environment.

12.1. Toxicity
No data available
12.2. Persistence and degradability
No data available
12.3. Bioaccumulative potential
No data available
12.4. Mobility in soil
No data available
12.5. Results of PBT and vPvB assessment
No data available
12.6. Other adverse effects
No data available

13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Do not allow into drains or water courses or dispose of where ground or surface waters may be affected. Wastes, including emptied containers, are controlled wastes and should be disposed of in accordance with regulations made under the Control of Pollution Act and the Environmental Protection Act. Empty containers must be scrapped or reconditioned. The European waste code voor this product is 08.01.12 (or 01.12.14 in flocculated form) according to Directive 2000/532/EC. Contact your local hazardous waste handler for further information.

14. TRANSPORT INFORMATION

Transport within the user's premises:

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

This product is NOT classified as dangerous for transport in the meaning of international transport regulations (ADR/RID, IMDG, ICAO/IATA).

14.1. UN number	-			
14.2. UN proper shipping name	-			
14.3. Transport hazard class(es)	-			
14.4. Packing group	-			
14.5. Environmental hazards	-			
14.6. Special precautions for user				
None				
14.7 Transport in hulk according to Appen II of MARPOL 72/78 a				

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable



15. REGULATORY INFORMATION

EU Legislation: The information in this Safety Data Sheet is in accordance with:

- Annex II of the REACH Regulation (EC) No. 1907/2006

- EU Directive 1999/45/EC

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Limit for this product (cat.A/d): 150 g/l (2007) / 130 g/l (2010):

VOC-content 60 - 70 g/l

15.2. Chemical Safety Assessment

A chemical safety assessment hasn't been performed.

"The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work."

16. OTHER INFORMATION

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC

Full text of R-phrases and Hazard Statements appearing in section 3: R65: Harmful: may cause lung damage if swallowed. R66: Repeated exposure may cause skin dryness or cracking.

Full text of L-phrases that apply on this product:

Revisions compared to the previous version: New product

SDS number

050000EN

The information of this SDS is based on the present state of our knowledge and on current EU and national laws. The product is not to be used for other purposes than those specified under section 1 without first obtaining written handling instruction. It is always the responsibility of the user to take all necessary steps in order to fulfill the demand laid down in the local rules and legislation. The information in this SDS is meant as a description of the safety requirements of our product: it is not to be considered as a guarantee of the products' properties.